PATENT CLAIMS

- 1. Windshield wiper device, in particular for a motor vehicle, comprising a securing part (10), which is used to secure a wiper arm to a wiper shaft (13), characterized in that the position of the wiper arm can be adjusted in a transversal manner in relation to the wiper shaft (13) by means of the securing part (10).
- 2. Windshield wiper device according to Claim 1, characterized in that securing part (10) has a lower part (11) and an upper part (12) that can be displaced relative thereto.
- 3. Windshield wiper device according to Claim 2, characterized in that the lower part (11) and the upper part (12) are provided with grooves (21, 30) that can engage in one another.
- 4. Windshield wiper device according to Claim 2 or 3, characterized in that the upper part (12) has a recess (22) to accommodate the lower part (11).
- 5. Windshield wiper device according to one of Claims 2 through 4, characterized in that the upper part (12) has an elongated hole (24) for inserting the wiper shaft (13).
- 6. Windshield wiper device according to one of Claims 2 through 5, characterized in that the lower part (11) has a hole (32) for inserting the wiper shaft (13).

- 7. Windshield wiper device according to Claim 6, characterized in that the hole (32) in the lower part (11) is conical.
- 8. Windshield wiper device according to one of Claims 2 through 7, characterized in that the upper part (12) features another recess (20) to accommodate a nut (14) or a screw head.